



EQUITY FACADE

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_{cw} ≥ 0.6 (W/m²K)

Please consult typology, dimensions and glazing

SECTIONS	Mullion 18 mm Transom 18 mm
----------	--------------------------------

PROFILE THICKNESS	2.6 mm (Mullion and Transom)
-------------------	------------------------------

Please consult maximum dimensions according to types

OPTIONS FOR COVERS
Flat cover
85 mm deep elliptical cover
H shape cover, 34 mm deep
Rectangular cover: 14, 19 100 & 145 mm deep
Pyramid shape cover, 155 mm deep

ACCOUSTIC INSULATION

Maximum glazing: **64 mm**

Minimum glazing: **4 mm**

EXTRUSION ALLOY
6063 T-6

THERMAL BREAK
6, 12 & 30 mm stackable thermal break profiles

GASKETS EPDM
Optionally Totally Vulcanized Corner Gasket

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

