



SKYLIGHT VERANDA

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient
U_{cw} ≥ 0.6 (W/m²K)

Please consult typology, dimensions and glazing.

GLAZING

Fixed lights:

Maximum glazing: 50 mm

Minimum glazing: 24 mm

Window roof:

Maximum glazing: 38 mm

Minimum glazing: 24 mm

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12152):

Class AE

Water tightness (EN 12154):

Class RE1350

Wind resistance (EN 13116):

PASSED Design loading 1200 Pa-Security loading 1800 Pa

Reference test 3.00 x 3.50 m

PROJECTING OPENING TEST

Air permeability (EN 12152):

Class 4

Water tightness (EN 12154):

Class RE2100

Wind resistance (EN 13116):

Class C5

Reference test window 1.23 x 1.14 m / 1 Sash

SECTIONS INWARDS	Mullion 52 mm Transom 52 mm	EXTRUSION ALLOY	6063 T-6
PROFILE THICKNESS	Mullion 2.1 and 3.0 mm Transom 2.1 mm	OPENING POSSIBILITIES	OUTWARD: Motorized top hung projecting
SLOPE	Minimum incline / slope Pt = 12% (7°) Maximum incline/slope = 85% (40°)	MAXIMUM DIMENSIONS	Top Hung Opening Width máx: 2.100 mm Width min 650 mm Height máx: 2.000 mm Height min 650 mm
MAXIMUM WEIGHT/SASH	Top Hung Opening 150 Kg		

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

